



Degreasing Fluid

Emulsifiable Degreasing Solvent Cleaner

Degreasing Fluid is an emulsifiable solvent degreaser developed for easy, safe and effective cleaning containing a blend of emulsifiers and penetrants in a solvent suitable for cleaning stubborn tar, oil and grease soils.

Features & Benefits

- Excellent penetration and cleaning for the most stubborn of soils
- Excellent emulsification and flushing

Applications

Degreasing Fluid can be applied neat or pre-mixed as emulsion for brush, swab, or spray type applications. If applied in the neat state the surface can be washed down with water.

Degreasing Fluid is ideal for use on bare metal and painted surfaces and stone or concrete floors.

Typical Physical Data

Relative Density (kg/m ³ @15 °C)	0.810
Kinematic Viscosity (Cst@40°C)	1.85
Closed Flash Point (PMCC °C)	46
pH Value @ 10% Emulsion	6.6

Safety information sheets are available for all Optimum products from the address below:

1 Ullenwood Court · Ullenwood · Cheltenham · Gloucestershire · GL53 9QS
 Head Office: 01242 253 333 · Customer Services & Orders: 08719 188 881 · Fax: 08719 189 998
 Email: technical@optimumoils.com · Web: www.optimumoils.com

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the date of printing. The above information may be affected by changes occurring subsequent to the date of printing in the formulation and its application for the products referred to or in the requirements of any specification or approval relating to any such products.