

Q8 Axle Oil XG 80W-140

SAE J2360 axle fluid

Description

Q8 Axle Oil XG 80W-140 is a high performance synthetic fluid providing excellent durability and performance for rear axles and final drives. This product provides extended drain intervals, thus reduces overall operating costs and vehicle maintenance. It meets the performance credentials of SAE J2360 and the requirements of top European OEMs and component manufacturers such as Scania and ZF.

Applications

Q8 Axle Oil XG 80W-140 is recommended for use in rear axles and final drive applications and is approved by Scania to use with extended drain intervals up to 180,000km. It meets the requirements of SAE J2360, top European OEMs and component manufacturers such as ZF.

Benefits

- Outstanding protection against wear and extends component life.
- Outstanding axle wear protection.
- Outstanding protection against rust and corrosion.
- Outstanding elastomer compatibility

Specifications, recommendations and approvals

API	GL-4	Scania	STO 1:0
API	GL-5	ZF	TE-ML 05A
API	MT-1	ZF	TE-ML 12M
MIL	PRF-2105E	ZF	TE-ML 16D
SAE	J 2360	ZF	TE-ML 21A

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,907
Viscosity Grade	-	-	SAE 80W-140
Kinematic Viscosity, 40 °C	D 445	mm ² /s	302
Kinematic Viscosity, 100 °C	D 445	mm ² /s	31
Viscosity Index	D 2270	-	142
Brookfield Viscosity, -26 °C	D 2983	Pa.s	140
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	178

The figures above are not a specification. They are typical figures obtained within production tolerances.